



This drawing and the technical information included in the drawing are property of Wavin-Labko Ltd. This drawing can not be shown to a third party without the consent of Wavin-Labko Ltd.

Approved by customer:

200

h = Connection height from ground (mm)      Nominal flow rate: 125 l/s  
 h = \_\_\_\_\_ mm      Max. flow rate: 375 l/s

9	ACCESSORY: Flooting adjustable cover Ø800, D400 (40 tn) (x)	<input type="checkbox"/>			
8	Ventilation outlet (as needed)	PE	D110		1
7	EuroHUK 800 maintenance shaft (as needed), material: PE-MD				1
	h = Connection height from ground (mm)				
	EuroHUK 800 h 9-13 (x)	<input type="checkbox"/>		Note! h=2100...2500 mm	
	EuroHUK 800 h13-17	<input type="checkbox"/>		Note! h=2500...2900 mm	
	EuroHUK 800 h17-21	<input type="checkbox"/>		Note! h=2900...3300 mm	
	EuroHUK 800 h21-25	<input type="checkbox"/>		Note! h=3300...3700 mm	
6	Flow regulator (Max. flow 125 l/s)				1
5	Maintenance shaft installation sleeve	GRP	D1000/1100 mm		1
4	Bypass outlet sewer	PVC	D500		1
3	Outlet sewer (max. 125 l/s)	PVC	D400		1
2	Inlet sewer (max. 375 l/s)	PVC	D500		1
1	Material: Glass Reinforced Plastic (GRP) "Lasa Composit", Ø2200/2370 pH3-10/Heat resistance 50°C				1

Product:

Title: LABKO FRW 125/375 Flow Regulator Well

Drawing type  
CUSTOMER DRAWING

Design by:      Checked by:      Approved by:      Drawing no.      Date:      Scale:

TIS/TL

JP 10.10.07

42JB01de

10.10.07

WAVIN-LABKO Ltd.

Construction site:



WAVIN-LABKO Ltd.  
 Labkote 1  
 FIN-36240 KANGASALA  
 FINLAND  
 Tel. +358-020-1285 200  
 Fax +358-020-1285 280

Construction site:

Construction site:

