



Selection of maintenance shaft EuroHUK 800 for FRW Direct NS40 – NS50			
EuroHUK 800 maintenance shaft model	h9-13 <input type="checkbox"/>	h13-17 <input type="checkbox"/>	h21-25 <input type="checkbox"/>
Installation depth from inlet to ground surface	1300-1700 mm	1700-2100 mm	2100-2500 mm

Selection of maintenance shaft EuroHUK 800 for FRW Direct NS65 – NS150			
EuroHUK 800 maintenance shaft model	h9-13 <input type="checkbox"/>	h13-17 <input type="checkbox"/>	h21-25 <input type="checkbox"/>
Installation depth from inlet to ground surface	1700-2100 mm	2100-2500 mm	2500-2900 mm

h = Separator connection height from ground
h = _____ mm

1	LABKO FRW Direct	NS	40	50	65	80	100	125	150
	Nominal flow rate	l/s	40	50	65	80	100	125	150
A	Inlet	D	315	315	400	400	400	400	400
B	Outlet	D	315	315	400	400	400	400	400
C	Bottom/inlet pipe	mm	700	700	900	900	900	900	900
D	Bottom/outlet pipe	mm	650	650	850	850	850	850	850
E	Ventilation outlet D110	pc	1	1	1	1	1	1	1
F	Diameter (ball)	mm	1780	1780	2170	2250	2250	2250	2250
G	Height	mm	1660	1660	2100	2200	2200	2200	2200
h _{min}	Min. connection height	mm	1300	1300	1700	1700	1700	1700	1700
h _{max}	Max. connection height	mm	2900	2900	3300	3300	3300	3300	3300
I	Flow regulator	mm	1	1	1	1	1	1	1
J	EuroHUK 800 Maintenance shaft (as needed)	pc	1	1	1	1	1	1	1
K	ACCESSORY: Cast iron cover Ø800 D400 (40 tn)	pc	1	1	1	1	1	1	1
	Material		PEM	PEM	PEM	PEM	PEM	PEM	PEM
	Chosen LABKO FRW	(x)	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Product: Title: LABKO® FRW Direct NS40-NS150

Design by: JP/TL Checked by: JP Approved by: 07.01.09 Drawing no. 42EB050e Date: 07.01.09 Scale: Drawing type CUSTOMER DRAWING

This drawing and the technical information included in the drawing are property of Wavin-Labko. All the national regulations concerning this product have to be checked before purchase of the product. Installation have to be done according to installation manual.

Approved by customer: _____ / _____ 200__



WAVIN-LABKO
Labkote 1
FIN-36240 KANGASALA
FINLAND
Tel. +358-(0)20-1285 200
Fax +358-(0)20-1285 280
www.wavin-labko.fi

Construction site: