



Part nro	Chosen (x)	Product	Part no.	pcs
	( )	Anchoring belt 6 m (polyester, 2000 kg)		4
4	( )	Floating adjustable cast iron cover D600	3 325 010	1
		Cast iron cover according to loading		1
	( )	A15 (1.5 tn)	3 322 050	
	( )	C250 (25 tn)	3 322 054	
	( )	D400 (40 tn)	3 322 056	
3	( )	Labcom Data Transfer Unit. More info <a href="http://www.wavin-labko.fi">www.wavin-labko.fi</a>		1
2		EuroHUK 600 maintenance shaft, material PE-MD		1
		h= Installation depth of separator from ground surface (mm)		
	( )	EuroHUK 600 h9-13, h= 900...1300 mm	3 632 632	
	( )	EuroHUK 600 h13-17, h=1300... 1700 mm	3 632 634	
	( )	EuroHUK 600 h17-21, h=1700...2100 mm	3 632 636	
	( )	EuroHUK 600 h21-25, h=2100...2500 mm	3 632 638	
		T Ventilation pipe, PE, D110, 1 pc		

1 EuroPEK OMEGA		3/L	6/S	10	15
Part no.		3 632 185	3 632 187	3 632 191	3 632 193
Maximum flow rate	l/s	3	6	10	15
A Inlet and outlet sewers	D	110	160	160	200
B Bottom/inlet	mm	1 280	1 280	1 280	1 730
C Bottom/outlet	mm	1200	1200	1200	1650
D Diameter of the tank	D	1780	1780	1780	2170
E Height	mm	1650	1650	1650	2100
F Effective capacity	l	2000	2000	2000	4000
G Oil storage capacity	l	280	280	280	380
H Sludge storage capacity	l	950	650	separate	separate
I Coalesator: 3-D filter	pcs	1	1	1	1
J Labko SET-2000 Hi Level/Oil -alarm unit	pcs	1	1	1	1
K Oil skimming pipe	pcs	1	1	1	1

This drawing and the technical information included in the drawing are prop of Wavin-Labko Ltd. This drawing can not be shown to a third party without the consent of Wavin-Labko Ltd.

Title: EuroPEK OMEGA oil separator  
 Design by: TÄ/JP Approved by: TiS 24.03.2006 Drawing no. 25AB01fe  
 Drawing type: Customer Drawing  
 Date: 23.03.2006 Scale (A4): 1:20  
 Construction site:

WAVIN-LABKO LTD  
 Labkotie 1  
 FIN-36240 KANGASALA  
 FINLAND  
 tel. + 358 20 128 5200  
 fax. + 358 20 128 5280