



EuroPEK Roo Kombi NS3/300
Oil separator, I-class (EN858)
Wno: 8535603



09
 EN 858-1

Fulfilled requirements of flow rate test according to standard EN858 (LGA)

Safety in case of fire: E
 VTT test report VTT-S-7683-06

h = Connection height from ground surface)
 h = _____ mm (900...2500 mm)

C	Sludge storage volume		300 l	
B	Effective volume		1000 l	
A	Oil storage volume (height 150 mm)		150 l	
10	ACCESSORY: LABCOM Data transfer unit (x)	<input type="checkbox"/>		
9	OilSET-1000 oil alarm unit			1
9a	SET/DM3 -probe			1
8	ACCESSORY: Floating adjustable cover D600, standard EN124			
	Cover class A15 1.5 tn (x)	<input type="checkbox"/>	Part no. 3322 050	
	Cover class C250 25 tn	<input type="checkbox"/>	Part no. 3322 054	
	Cover class D400 40 tn	<input type="checkbox"/>	Part no. 3322 056	
	Frame	<input type="checkbox"/>	Part no. 3325 010	
7	EuroHUK 600 Maintenance shaft (as needed), PE-MD h = connection height from ground surface (mm)			1
	EuroHUK 600 h= 9-13 (x)	<input type="checkbox"/>	h= 900...1300 mm	
	EuroHUK 600 h=13-17	<input type="checkbox"/>	h=1300...1700 mm	
	EuroHUK 600 h=17-21	<input type="checkbox"/>	h=1700...2100 mm	
	EuroHUK 600 h=21-25	<input type="checkbox"/>	h=2100...2500 mm	
6	Ventilation outlet (as needed)	PE	D110	1
5	Coalescer		H=700 mm	2
4	Fuel suction pipe	PVC	D160	1
3	Outlet sewer	PE-HD	D110	1
2	Inlet sewer	PE-HD	D110	1
1	Tank (pH3-10/Heat resistance max. 50°C)	PE-MD	1320x1600 mm	1

This drawing and the technical information included in the drawing are property of Wavin-Labko Ltd. Authorities' regulations must be known before providing the product. Products must be installed according to installation instructions.



Product: EuroPEK Roo Kombi NS3/300 oil separator Drawing type: CUSTOMER DRAWING

Design by: TP/TL Approved by: JP 05.01.2010 Drawing no: 29PB03_e Date: 05.01.2010 Scale (A4): 1:30



WAVIN-LABKO Ltd.
 Labkotie 1
 FIN-36240 KANGASALA
 FINLAND
 puh. +358 020 1285 200
 fax. +358 0201285 280

Construction site: